# FORESTRY MULCHERS FOR SKID STEERS UML/SSL/VT/BL - UML/SSL/BL/SONIC

Forestry mulcher with Bite Limiter rotor system.

Robust and compact, the UML/SSL/VT/BL - UML/SSL/ BL/SONIC is renowned for its ergonomic design that guarantees excellent visibility for the operator during various situations.

The VT version with automatic variable displacement hydraulic motor increases productivity by up to 50% and simultaneously reduces fuel consumption.

**Rotor Bite Limiter** 





### Sonic System

is a new automatic intelligent system that manages the hydraulic transmission. It makes the mulching machine to perform at the maximum capacity in all conditions (UML/SSL/BL/SONIC)

**Reinforced frames** Provides extra protection from the power of the carrier





## MAIN OPTIONS



**Customized setting** hydraulic motor



## STANDARD EQUIPMENT

110/60cc variable torque hydraulic piston motor (32-53 gpm) (UML/SSL/VT/BL)		
Adjustable skids		
Safety and anticavitation valve		
Enclosed / anti dust machine body		
Motor enclosed in the frame		
Belt transmission (Poly Chain®)		
Hydraulic hoses		
Rear deflector		
OPTIONS		
Customized setting hydraulic motor (UML/SSL/VT/BL)		
Oil cooler kit		
Case drain required		
MODEL	UML/SSL/VT/BL 150	
Power (hp)	75-120	
Flow rate (gal/min)	32-53	
Pressure (PSI)	2900-5000	
Working width (in)	62	
Total width (in)	74	
Weight (lbs)	2866	
Rotor diameter (in)	16.5	
Max shredding diameter (in)		
Max silledding diameter (m)	8	

Data refers to machine as standard set-up. Options may have reflects on weights and dimensions. The technical data in this catalogue may be altered without prior notice.

#### **ROTOR TYPE BL**





C/3/SS (side scraper)

(option)

**No. blades** type BL + C/3/SS



110cc variable torque hydraulic piston motor (32-53 gpm) (UML/SSL/BL/SONIC)
Working pressure control gauge
Guard frame
Dual row protection chains
Welded counterblades
Rotor Bite Limiter
Sonic System (UML/SSL/BL/SONIC)
Adaptor wiring

Universal cabin roof hydraulic oil cooler kit

UML/SSL/VT/BL 175	UML/SSL/BL/SONIC 150	UML/SSL/BL/SONIC 175
75-120	75-120	75-120
32-53	32-53	32-53
2900-5000	2900-5000	2900-5000
72	62	72
83	74	83
3086	2866	3086
16.5	16.5	16.5
8	8	8
30+2	24+2	30+2

24+2